



**ACRYLOCOAT™** brand *Brush/Roller/Spray Applied*  
**ACRYLOTEX™**  
*Decorative Fine or Coarse Texture Coating*

**PRODUCT DATA**  
**12 YEAR LIMITED MATERIAL WARRANTY**  
**#70070**  
**01/12/09**  
*superseding: 02/13/07*

**ACRYLOTEX™ PRODUCT DESCRIPTION:**

ACRYLOCOAT™ brand ACRYLOTEX™ is One Part of the Multi-Stage ACRYLOCOAT™ Decorative Finish Protective Coating System. ACRYLOTEX™ is a Waterproofing Elastomeric Ceramic Decorative Finish Texture Coating. This easy to use Texture Coating is an Acrylic Elastomeric, Insulating Ceramic Formulation that creates a Brush, Roller or Spray Applied (using proper spray equipment) Sand Cement Like or Coarse Stucco Like Finish as an Exterior Decorative Finish System. When applied in conjunction with ACRYLOCOAT™ brand ACRYLOPRIME™ and ACRYLOSEAL™, it seals and forms a waterproofing, flexible, breathable finish that has outstanding durability. ACRYLOTEX™ will expand and contract with varying hot and cold temperatures, plus resist thermal shock. Unsurpassed in technology, ACRYLOTEX™ offers superior mildew resistance, corrosion resistance, ceramic insulation and soundproofing, excellent adhesion, ultraviolet ray reflectivity and a beautiful flat finish. ACRYLOTEX™, used as part of the ACRYLOCOAT™ brand system, has been designed to replace cementitious finishes and combat the destructive environmental forces of nature. The ACRYLOCOAT™ brand Product Line is generally an Exterior Decorative Coating System, but can be used on Interior Surfaces as well. A TWELVE YEAR LIMITED MATERIAL WARRANTY against chipping, cracking and peeling is available only when applied as part of the ACRYLOCOAT™ Decorative Finish Protective Coating System. Inquire about the Detailed Application Procedure.

**ACRYLOTEX™ APPLICATION USES:**

ACRYLOTEX™ can be used on most any Interior or Exterior Substrate including: wood, primed metal, galvanized, primed synthetic or aluminum siding, tin, copper, asbestos, asphalt, urethane, polyester, styrofoam, foam, fiberglass, clay, adobe, brick, stucco, slate, cement block, poured concrete, slab and various other substrates. The ACRYLOCOAT™ brand Product Line is excellent to decorate and enhance the exterior walls and facades of buildings, homes, and facilities including: residential, commercial and industrial applications.

**ACRYLOTEX™ DECORATIVE FINISH COLORS:**

ACRYLOTEX™ comes standard in White, Only. Colors are achieved by applying tinted ACRYLOSEAL™ or ACRYLOSATIN™ to the ACRYLOTEX™. NOTE: Even if the desired color is white, a coat of white ACRYLOSEAL™ or ACRYLOSATIN™ is required over ACRYLOTEX™.

**ACRYLOTEX™ SURFACE PREPARATION:**

If ACRYLOTEX™ is used in the 12 Year Warranted ACRYLOCOAT™ Decorative Finish Protective Coating System, please inquire for a detailed application procedure sheet and strictly follow the application method. If Applicable, trenching is necessary to form a complete seal; trench 4 to 6 inches around the perimeter of the structure. For proper adhesion to an existing substrate, it is essential that the surface be pressure washed at a minimum of 1500 P.S.I., using a water and chlorine solution, removing any loose, flaking or peeling paint along with any dirt, oil, grease, residues and especially mold, mildew and algae. Wire brush if necessary. Apply only to a sound, well prepared wall surface. Rusted metal must be primed. Inquire about METAL-PRIME Rust Treatment Process. Patch any holes, cracks, seams, imperfections, etc., with ACRYLOPATCH™ Waterproofing Caulk & Sealant. It is recommended to use ACRYLOPRIME™ before application of ACRYLOTEX™, and a coat of ACRYLOSEAL™ or ACRYLOSATIN™ over the coat of ACRYLOTEX™. Wait 12 hours between coats of any of the ACRYLOCOAT™ product line.

**ACRYLOTEX™ APPLICATION PROCEDURE:**

Do not thin, use product as is. Do not apply when temperatures are below 45 degrees Fahrenheit or when humidity is very high. Apply ACRYLOTEX™ by brush, roller or Hopper type spray equipment to the prepared surface. Clean all tools and equipment immediately after use with warm soapy water.

**TECHNICAL SPECIFICATIONS:** Ambient Temperature of 77°F and RH of 50%

|                      |                             |                |                       |
|----------------------|-----------------------------|----------------|-----------------------|
| FINISH:              | Fine or Sand                | SPREAD RATE:   | 40 to 75 sq.ft./gal.  |
| COLOR:               | White (Not-Tintable)        | DRY to TOUCH:  | 2 to 4 Hours          |
| VEHICLE TYPE:        | Acrylic Copolymer Emulsion  | RECOAT:        | 12 Hours              |
| SOLIDS by WEIGHT:    | 64% +/- 2%                  | CURE TIME:     | 5 to 7 Days           |
| SOLIDS by VOLUME:    | 46% +/- 2%                  | SIZES:         | 5 Gallon              |
| V.O.C.'s (averages): | n/a lbs./gal. • n/a g/liter | GALLON WEIGHT: | 11.6 lbs. +/- .3 lbs. |

Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.



# MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL DATA SHEET

**MSDS#:  
70070**

|   |   |  |
|---|---|--|
| <b>Product Identification</b>           | Product Name: <b>ACRYLOCOAT™ brand ACRYLOTEX™</b><br>Product Code #: 70070<br>General Usage: Latex Wall Texture Coating<br>General Description: Pigmented Latex Decorative Wall Texture Coating<br>C.A.S. Number: None Established; Mixture   |  |
| <b>Manufacturer Information</b>         | Manufacturer's Name: Nationwide Chemical Coating Mfrs., Inc.<br>Address: 7106 24th Court East; Sarasota, FL 34243-3993<br>Emergency Telephone: 1-800-423-7264 or 941-753-7500<br>Information: 1-800-423-7264 or 941-753-7500<br>Web Site: www.nationwidecoatings.com E-Mail: info@natcoat.net<br>Date Effective: January 1 <sup>st</sup> , 2005 |  |
| <b>Chemical and Physical Properties</b> | Color: White<br>Physical State: Liquid<br>Boiling Point: 212 Fahrenheit<br>Specific Gravity (H <sub>2</sub> O=1): >1<br>Vapor Presence: about same as H <sub>2</sub> O<br>Percent Volatile: 31-36%<br>Evaporation Rate (Butyl Acetate=1): <1  | Odor: Pungent Odor<br>Odor Threshold: Unknown<br>Melting Point: N/A<br>Freezing Point: 32 Fahrenheit<br>Solubility in H <sub>2</sub> O: Soluble<br>pH (undiluted): 8 to 8.5<br>Vapor Density (Air=1): <1 |
| <b>Fire Protection Information</b>      | Decomposition/Combustion:<br>Flash Point:<br>Recommended Extinguishing Media:<br>Flammable Limits:  | N/A<br>N/A; Does Not Burn<br>N/A<br>N/A  |
| <b>Storage and Reactivity</b>           | Hazardous Polymerization:<br>Storage Conditions:<br>Toxic Products Which May Form:  | Will Not Occur<br>Keep from Freezing<br>None   |
| <b>Transportation</b>                   | Hazard Classes:<br>Hazard Labels:<br>Hazard Determination:<br>Shipping Containers:<br>Shipping Class:   | None; Not Hazardous<br>Not Required<br>MSD Sheet<br>Varies<br>Class 55; Water Based Paint  |
| <b>Container Labeling</b>               | Explanation of Unique Labeling System: None Used  |  |

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Health Hazard Data</b>         | <b>SHORT TERM EXPOSURE</b>   |   |
|                                   | Route of Entry:<br>Inhalation:<br>Skin:<br><br>Eyes:<br><br>Ingestion:   | Precautionary Treatment<br>Expected None<br>Expected None<br><br>Flush Immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists<br><br>Call a physician if significant amounts have been Swallowed. Give patient large amounts of water or milk for dilution. |
|                                   | <b>LONG TERM EXPOSURE</b>  |   |
|                                   | Carcinogen:<br>Target Organ Effects:<br>Other Health Hazards:  | None<br>None<br>None Known  |
| <b>Personal Protection</b>        | Respiratory Protection:<br>Protective Clothing:<br>Ventilation:<br>Other Protective Measures:<br>Eye Protection:   | No inhalation hazard expected<br>None Required<br>Local<br>None<br>Safety Glasses   |
| <b>Spill or Leak Protection</b>   | Accidental Release or Spill:<br><br>Neutralizing Chemical/Media:   | Collect liquid or solidify with absorbent package for disposal<br><br>N/A   |
| <b>Treatability</b>               | Biodegradability: With water prior to cure.<br>Influence on Biological Wastewater Treatment: None<br>Other Impacts on Wastewater Treatment: None<br>Recommended Wastewater Treatment: Dilutable<br>Constituents Interfering With or Not Amenable to Biological or Wastewater Treatment: None |   |
| <b>Recommended Waste Disposal</b> | Dispose of in accordance with Federal, State and Local guidelines.   |   |