



ACRYLOCOAT™ *brand Spray or Roll Applied*
ACRYLOPRIME™
ELASTOMERIC ACRYLIC WATERPROOFING
Light Gray Adhesive Bonding Primer

PRODUCT DATA
#70010
02/01/13
superseding: 11/02/12

15 YEAR LIMITED MATERIAL WARRANTY

ACRYLOPRIME™ PRODUCT DESCRIPTION:

ACRYLOCOAT™ brand **ACRYLOPRIME™** is One Part of the Multi-Stage **ACRYLOCOAT™** Decorative Finish Protective Coating System. **ACRYLOPRIME™** is a High Solids Acrylic Waterproofing Adhesive Resin Mixture, Elastomeric Bonding Primer. It is a Brush, Roller or Spray applied Prime Coat that prepares the surface for one of the **ACRYLOCOAT™** Exterior Decorative Finish Systems. When applied in conjunction with **ACRYLOSAND™** or **ACRYLOSTUK™**, it seals and forms a waterproofing, flexible, breathable finish that has outstanding durability. **ACRYLOPRIME™** revitalizes and strengthens the substrate to which it is applied, preventing cracking, efflorescence, spalling and segregation. An extremely high resin content provides for excellent adhesion to most any substrate creating a tight, permanent bond to the coating that it is applied over. This eliminates the possibility of moisture under the coating system that will extend the life of the **ACRYLOCOAT™** System considerably. **ACRYLOPRIME™** gives extra strength to the High Solids **ACRYLOCOAT™** Textures and its Elastomeric qualities greatly reduce the possibility of cracking in the finished system. The **ACRYLOCOAT™** brand Product Line is generally an Exterior Decorative Coating System, but can be used on Interior Surfaces as well.

ACRYLOPRIME™ APPLICATION USES:

ACRYLOPRIME™ can be used on most any Interior or Exterior Substrate including: wood, primed metal, galvanized, primed synthetic or aluminum siding, tin, copper, asbestos, asphalt, urethane, polyester, styrofoam, foam, fiberglass, clay, adobe, brick, stucco, slate, cement block, poured concrete, slab and various other substrates. The **ACRYLOCOAT™** brand Product Line is excellent to decorate and enhance the exterior walls and facades of buildings, homes and facilities including: residential, commercial and industrial applications.

ACRYLOPRIME™ FINISH:

ACRYLOPRIME™ comes standard in a Matte Light Gray Finish.

ACRYLOPRIME™ SURFACE PREPARATION:

If **ACRYLOPRIME™** is used in the 15 Year Warranted **ACRYLOCOAT™** Decorative Finish Protective Coating System, please inquire for a detailed application procedure sheet and strictly follow the application method. If Applicable, trenching is necessary to form a complete seal; trench 4 to 6 inches around the perimeter of the structure. For proper adhesion to an existing substrate, it is essential that the surface be pressure washed at a minimum of 1500 P.S.I., using a water and chlorine solution, removing any loose, flaking or peeling paint along with any dirt, oil, grease, residues and especially mold, mildew and algae. Wire brush if necessary. Apply only to a sound, well prepared wall surface. Rusted metal must be primed. Inquire about **METAL-PRIME RED-OX™** Rust Treatment Process. Patch any holes, cracks, seams, imperfections, etc., with **ACRYLOPATCH™** Waterproofing Caulk & Sealant prior to applying **ACRYLOPRIME™**. Wait 12 hours between coats of any of the **ACRYLOCOAT™** Product Line.

ACRYLOPRIME™ APPLICATION PROCEDURE:

Do not thin, use product as is from the container. Do not apply when temperatures are below 45 degrees Fahrenheit or when humidity is very high. Apply **ACRYLOPRIME™** with a Brush, Roller or Sprayer to the prepared surface. Clean all tools and equipment immediately after use with warm soapy water.

Ambient Temperature of 77°F and RH of 50%

TECHNICAL SPECIFICATIONS:

Rates & Times May Vary Beyond Specifications

FINISH:	Matte	SPREAD RATE:	150 to 200 sq.ft./gal.
COLOR:	Light Gray	DRY to TOUCH:	2 to 4 Hours
VEHICLE TYPE:	Copolymer Emulsion	RECOAT:	12 Hours
SOLIDS by WEIGHT:	50% +/- 2%	CURE TIME:	5 to 7 Days
SOLIDS by VOLUME:	41% +/- 2%	SIZES:	5 Gallon, 55 Gallon Drum
V.O.C.'s (averages):	.71 lbs./gal. • 85.0 g/liter	GALLON WEIGHT:	10.1 lbs. +/- .3 lbs.

Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.