



CLEAR BONDING ACRYLIC
SUPER BOND™
PVC/PLASTIC BONDER & ADHESIVE PRIMER
Great for HARD to PRIME Smooth Surfaces

PRODUCT DATA
#2575

07/11/12
superseding: 04/06/11

PRODUCT DESCRIPTION:

SUPER BOND™ is a fast drying clear acrylic bonding adhesive primer and surface conditioner with exceptional adhesion to most any surface. This high performance multi-use latex bonding primer dries to a hard finish and can be top coated with most any paint or coating. **SUPER BOND™** has superior adhesion for those hard to paint surfaces such as PVC pipe, most plastics, fiberglass, glass, aluminum, rubber roofs and galvanized metal. Works well for use as a chalk sealer and as a primer on previously painted surfaces.

PRODUCT USES:

SUPER BOND™ is a unique interior and exterior adhesive bonding primer for use on most any surface including: PVC pipe, many plastic substrates, fiberglass, glass, aluminum, galvanized and anodized metal. Excellent for use as a chalk sealer and bonding coat on previously coated masonry, stucco, wood and metal surfaces.

SUPER BOND™ Can be used as a primer on certain types of roof surfaces including: rubber roofs, EPDM (ethylene propylene diene monomer) and PVC roofs. **SUPER BOND™** is ideal for use on Residential, Commercial, Industrial and most other applications.

Note: Do not use **SUPER BOND™** on any type of unprimed ferrous metal, bare wood or new and uncoated masonry, stucco or plaster or any other uncoated cementitious surfaces.

SURFACE PREPARATION:

For proper adhesion it is essential that the surface is prepared properly.

Clean exterior surfaces to remove any previous peeling coatings, dirt, grease and other foreign materials, especially mold, mildew and algae by thoroughly pressure washing with a water and chlorine solution using at least 1500 P.S.I. Rinse thoroughly after cleaning and allow the surface to dry completely. Remove loose paint and powdery substances. Patch any holes, cracks, seams, imperfections, etc., with **PERMAPATCH™**, Waterproofing Caulk & Sealant.

Clean interior surfaces to wash off all dirt, grease, soap and oil build-up with a powdered household cleaner and water, then rinse or wipe off thoroughly with water using a damp cloth and allow the surface to dry thoroughly.

APPLICATION PROCEDURE:

Mix thoroughly before use. Do not thin, use product as is from container. May be applied by brush, roller or spray. Do not apply within 2 hours of expected rain or heavy dew. Do not apply when air or surface temperature is below 50 degrees and above 110 degrees Fahrenheit.

Chalk Sealing: To seal chalk, **SUPER BOND™** should be rolled and worked into the surface.

Note: Do not use **SUPER BOND™** on any type of unprimed ferrous metal, bare wood or new and uncoated masonry, stucco or plaster or any other uncoated cementitious surfaces. Do not let spatter cure on glass as it will etch the surface.

CLEAN UP:

Clean all spills and tools immediately after use while coating is wet with warm soapy water.

Ambient Temperature of 77°F and RH of 50%

TECHNICAL SPECIFICATIONS:

Rates & Times May Vary Beyond Specifications

FINISH:	Low Sheen	SPREAD RATE:	200 to 300 sq.ft./gal.
COLOR:	Clear	DRY to TOUCH:	30 Minutes
VEHICLE TYPE:	Acrylic Emulsion	RECOAT:	1 - 2 Hours
SOLIDS by WEIGHT:	20% +/- 2%	CURE TIME:	5 to 7 Days
SOLIDS by VOLUME:	18% +/- 2%	SIZES:	1 Gal., 5 Gal., 55 Gal.
V.O.C.'s (averages):	0.42 lbs./gal. • 50 g/liter	GALLON WEIGHT:	8.7 lbs. +/- .3 lbs.

Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.

In Any Event Nationwide Protective Coating Manufacturers, Inc. will not be liable or responsible for any past, present or future leaks or any resulting consequential or incidental damages.



MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL DATA SHEET

**MSDS#:
2575**

Product Identification	Product Name: SUPER BOND™ Product Code #: 2575 General Usage: Latex Bonding Primer General Description: Non-Pigmented Latex Primer C.A.S. Number: None Established; Mixture	
Manufacturer Information	Manufacturer's Name: Nationwide Protective Coating Mfrs., Inc. Address: 7106 24th Court East; Sarasota, FL 34243-3993 Emergency Telephone: 1-800-423-7264 or 941-753-7500 Information: 1-800-423-7264 or 941-753-7500 Web Site: www.nationwidecoatings.com E-Mail: info@natcoat.net Date Effective: January 1 st , 2011	
Chemical and Physical Properties	Color: Clear Physical State: Liquid Boiling Point: 212 Fahrenheit Specific Gravity (H ₂ O=1): >1 Vapor Presence: about same as H ₂ O Percent Volatile: 75-80% Evaporation Rate (Butyl Acetate=1): <1	Odor: Mild Odor Odor Threshold: Unknown Melting Point: N/A Freezing Point: 32 Fahrenheit Solubility in H ₂ O: Soluble pH (undiluted): 8 to 8.5 Vapor Density (Air=1): <1
Fire Protection Information	Decomposition/Combustion: N/A Flash Point: N/A; Does Not Burn Recommended Extinguishing Media: N/A Flammable Limits: N/A	
Storage and Reactivity	Hazardous Polymerization: Will Not Occur Storage Conditions: Keep from Freezing Toxic Products Which May Form: None	
Transportation	Hazard Classes: None; Not Hazardous Hazard Labels: Not Required Hazard Determination: MSD Sheet Shipping Containers: Varies Shipping Class: Class 55; Water Based Paint	
Container Labeling	Explanation of Unique Labeling System: None Used	

Health Hazard Data	SHORT TERM EXPOSURE	
	Route of Entry: Inhalation: Skin: Eyes: Ingestion:	Precautionary Treatment Expected None Expected None Flush Immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists Call a physician if significant amounts have been Swallowed. Give patient large amounts of water or milk for dilution.
	LONG TERM EXPOSURE	
	Carcinogen: None Target Organ Effects: None Other Health Hazards: None Known	
Personal Protection	Respiratory Protection: Protective Clothing: Ventilation: Other Protective Measures: Eye Protection:	No inhalation hazard expected None Required Local None Safety Glasses
Spill or Leak Protection	Accidental Release or Spill: Neutralizing Chemical/Media:	Collect liquid or solidify with absorbent package for disposal N/A
Treatability	Biodegradability: With water prior to cure. Influence on Biological Wastewater Treatment: None Other Impacts on Wastewater Treatment: None Recommended Wastewater Treatment: Dilutable Constituents Interfering With or Not Amenable to Biological or Wastewater Treatment: None	
Recommended Waste Disposal	Dispose of in accordance with Federal, State and Local guidelines.	

EMERGENCY & INFO: 1-800-423-7264

Form based on O.S.H.A. Form 20. Information presented herein has been compiled from sources to be reliable and is accurate and reliable to be the best of our knowledge and belief but is not guaranteed to be so.

EMERGENCY & INFO: 941-753-7500