



**ACRYLIC CERAMIC - LOW ODOR**  
**ENVIRO-4000®**  
**GREEN TECHNOLOGY - ZERO V.O.C.**  
**EXTERIOR WALL & TRIM PAINT**

**PRODUCT DATA**  
**15 YEAR LIMITED MATERIAL WARRANTY**  
**#2000**  
**#2025**  
**#2050**  
**01/26/16**  
*superseding: 07/16/10*

**PRODUCT DESCRIPTION:**

ENVIRO-4000® is a low odor, Zero V.O.C.\* (Volatile Organic Compound), high quality, insulating ceramic, wall and trim house paint. It is formulated with acrylic resin and ceramic fillers, that provide insulating and soundproofing values along with a uniform, easy to apply, excellent hiding beautiful latex finish. ENVIRO-4000® possesses excellent Mildew Resistance and Antibacterial Properties. When applied according to specifications, ENVIRO-4000® offers a 15 YEAR LIMITED MATERIAL WARRANTY.

*\* This paint is described as "Zero V.O.C." because it doesn't contain any of the solvents that are normally used in conventional latex paints. Trace amounts of V.O.C.s may be present as residual components of other ingredients although the total V.O.C. content will still be negligible.*

**ENVIRO-4000® USES:**

For use on walls and trim over a wide variety of surfaces, such as: exterior wood, concrete, brick, masonry, stucco, primed metal, and primed synthetic or aluminum siding. It is excellent for apartments, condominiums, warehouses, motels, offices & residential dwellings.

**HIGH PERFORMANCE FEATURES:**

- Soundproofing & Insulating Values
- High Solids Modified Acrylic Vehicle
- Excellent Exterior Durability
- Excellent Scrub Resistance
- Stain & Dirt Pick Up Resistance
- Excellent Freeze-Thaw Stability
- Excellent Leveling and Touch Up
- Highly Water Resistant
- Easy Application & Water Clean Up
- 15 YEAR LIMITED MATERIAL WARRANTY

**SURFACE PREPARATION:**

**PREVIOUSLY PAINTED SURFACES:**

Thoroughly clean surface of dirt, oil, grease, chalk or foreign matter by scraping, sanding, scrubbing and/or rinsing. Scrape off any loose, blistering, cracking or peeling paint using a wire brush and scraper. If peeling is extensive, strip, sand and prime the entire surface area. Sand all glossy surfaces before washing. This paint will resist mildew growth, but will not kill spores, which are nearly invisible and must be removed prior to painting. Scrub soiled, chalky or mildewed surfaces with a solution of one cup detergent, one quart household bleach and one gallon of water. Protect shrubbery and grass. Wash house from bottom up including eaves, soffit and fascia. The complete surface to be painted must be cleaned even if it looks clean, because invisible residues may cause peeling. Rinse surface thoroughly. Let dry 24 hours.

**UNPAINTED SURFACES:**

For best results use ENVIRO-4000® Primer Sealer, before applying paint (may not seal stains).

**Wood:** Prime bare wood with one or two coats of Primer Sealer depending on condition of the surface. Sand weathered or discolored wood down to solid wood. Clean free of all dust, then prime. Wood knots should be spot primed with shellac. Pressure treated wood must be aged at least 6 months before it can be primed.

**Metal:** Clean surface of all grease, oil and foreign matter before priming. Rusted metal and galvanized metal must be primed with METAL-PRIME RED-OX™, a Red Iron Oxide Primer Sealer.

**Masonry:** Prime masonry before painting. New masonry must either be sealed with CHALK-FORCE™ or aged 60 days before priming.

**APPLICATION PROCEDURE:**

Stir well before using. Thinning is not recommended but if necessary use water sparingly. Do not apply when temperatures are below 40 degrees Fahrenheit or when humidity is very high. Do not apply when paint will be subjected to rain or heavy dew.

Apply using brush, roller or spray. When rolling, apply in an "N" pattern first, then cross roll to spread paint, and finish with light roller strokes in downward direction. Always roll or brush from untouched into wet paint areas. Allow at least 4 hours to dry before applying a second coat. Spread uniformly. Two coats are required for the 15 Year Limited Material Warranty, and a Warranty Registration Certificate must be received by Nationwide within 90 days of paint application (inquire for details). Wait at least two weeks before washing the dry paint film. Coverage depends upon surface and porosity; 200 – 350 square feet per gallon.

**CLEAN UP:**

Clean up all spills, tools and overspray immediately while the coating is still wet with warm soapy water.

Ambient Temperature of 77°F and RH of 50% **TECHNICAL SPECIFICATIONS:** Rates & Times May Vary Beyond Specifications

FINISH:	Flat • Satin • Semi-Gloss	SPREAD RATE:	200 to 350 sq.ft./gal.
COLOR:	White, Deep & Clear Base	DRY TO TOUCH:	2 to 4 Hours
VEHICLE TYPE:	Copolymer Emulsion	RECOAT:	4 Hours
SOLIDS by WEIGHT:	52% +/- 5%	CURE TIME:	5 to 7 Days
SOLIDS by VOLUME:	36% +/- 5%	SIZES:	1 Gal., 5 Gal., 55 Gal.
V.O.C.'s (averages):	0 lbs./gal. • 0 g/liter	GALLON WEIGHT:	11.7 lbs. +/- .3 lbs.

Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.



# MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL DATA SHEET

**MSDS#:**

2000  
2025  
2050

<b>Product Identification</b>	Product Name: <b>ENVIRO-4000® Paint</b> Product Code #: <b>2000, 2025 &amp; 2050</b> General Usage: Exterior Latex Paint General Description: Pigmented Latex Paint C.A.S. Number: None Established; Mixture	
<b>Manufacturer Information</b>	Manufacturer's Name: Nationwide Protective Coating Mfrs., Inc. Address: 7106 24th Court East; Sarasota, FL 34243-3993 Emergency Telephone: 1-800-423-7264 or 941-753-7500 Information: 1-800-423-7264 or 941-753-7500 Web Site: www.nationwidecoatings.com      E-Mail: info@natcoat.net Date Effective: January 1 <sup>st</sup> , 2005	
<b>Chemical and Physical Properties</b>	Color: White Physical State: Liquid Boiling Point: 212 Fahrenheit Specific Gravity (H <sub>2</sub> O=1): >1 Vapor Presence: about same as H <sub>2</sub> O Percent Volatile: 43-53% Evaporation Rate (Butyl Acetate=1): <1	Odor: No Odor Odor Threshold: Unknown Melting Point: N/A Freezing Point: 32 Fahrenheit Solubility in H <sub>2</sub> O: Soluble pH (undiluted): 8 to 8.5 Vapor Density (Air=1): <1
<b>Fire Protection Information</b>	Decomposition/Combustion: Flash Point: Recommended Extinguishing Media: Flammable Limits:	N/A N/A; Does Not Burn N/A N/A
<b>Storage and Reactivity</b>	Hazardous Polymerization: Storage Conditions: Toxic Products Which May Form:	Will Not Occur Keep from Freezing None
<b>Transportation</b>	Hazard Classes: Hazard Labels: Hazard Determination: Shipping Containers: Shipping Class:	None; Not Hazardous Not Required MSD Sheet Varies Class 55; Water Based Paint
<b>Container Labeling</b>	Explanation of Unique Labeling System:      None Used	

<b>Health Hazard Data</b>	SHORT TERM EXPOSURE	
	Route of Entry: Inhalation: Skin: Eyes: Ingestion:	Precautionary Treatment Expected None Expected None Flush Immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists Call a physician if significant amounts have been swallowed. Give patient large amounts of water or milk for dilution.
	LONG TERM EXPOSURE	
	Carcinogen: Target Organ Effects: Other Health Hazards:	None None None Known
<b>Personal Protection</b>	Respiratory Protection: Protective Clothing: Ventilation: Other Protective Measures: Eye Protection:	No inhalation hazard expected Apron to keep off Clothes Local None Safety Glasses
<b>Spill or Leak Protection</b>	Accidental Release or Spill: Neutralizing Chemical/Media:	Collect liquid or solidify with absorbent package for disposal N/A
<b>Treatability</b>	Biodegradability: With water prior to cure. Influence on Biological Wastewater Treatment: None Other Impacts on Wastewater Treatment: None Recommended Wastewater Treatment: Dilutable Constituents Interfering With or Not Amenable to Biological or Wastewater Treatment: None	
<b>Recommended Waste Disposal</b>	Dispose of in accordance with Federal, State and Local guidelines.	

**EMERGENCY & INFO: 1-800-423-7264**

*Form based on O.S.H.A. Form 20. Information presented herein has been compiled from sources to be reliable and is accurate and reliable to be the best of our knowledge and belief but is not guaranteed to be so.*

**EMERGENCY & INFO: 941-753-7500**