



**ELASTOMERIC**  
**KOOL-KOTE™**  
**REFLECTIVE**  
**ROOF COATING**

**PRODUCT**  
**DATA**  
**#7000**

**03/27/13**  
*superseding: 03/30/10*

**PRODUCT DESCRIPTION:**

**KOOL-KOTE™** is a bright white, modified acrylic blend elastomeric, reflective, waterproofing roof coating. It is a waterborne, latex based, high build, waterproofing formula that beautifies and protects. **KOOL-KOTE™** helps seal and prevent most small leaks, but is not guaranteed to do so. It forms a rubber-like shield of protection that expands and contracts with varying hot and cold temperatures, plus resists thermal shock. **KOOL-KOTE™** offers good mildew resistance, bright white reflectivity, excellent adhesion and a beautiful finish. It has been designed as a reflective coating to save on energy during the hotter seasons of the year. This easy to apply roof coating will provide years and years of durable protection, outstanding beauty, and will actually extend the life of the roof.

**KOOL-KOTE™ USES:**

**KOOL-KOTE™** is recommended for well drained, SLOPED roof surfaces only (minimum of 2 degrees or 1" per 2 foot slope). It has excellent adhesion on weathered wood, shakes, plywood, primed metal, galvanized, aluminum, tin, copper, asbestos, asphalt, urethane, polyester, styrofoam, fiberglass, built up roofs, bonded roof gravel, rolled roofing, modified bitumen membranes, mineral surfaced roofing, stucco, concrete tiles, clay tiles, masonry tiles (flat or barrel), slate, slab and various other substrates. **KOOL-KOTE™** is intended for residential, commercial and industrial applications.

**HIGH PERFORMANCE FEATURES:**

**KOOL-KOTE's™** high reflectivity saves on energy. It's beautiful bright white finish can be tinted to pastels & light colors. It extends roof life and features easy application and water clean up. It is also safe for the environment.

**SURFACE PREPARATION:**

If the roof surface to be coated was previously coated, if leaks were previously present, or if the roof surface requires extra bonding; a primer sealer coat of **ROOF-PRIME™** or **PERMABOND™** is recommended prior to the application of **KOOL-KOTE™**. For proper adhesion it is essential that the surface be clean and dry and free of all moisture. Prepare the surface by thoroughly pressure washing with a water and chlorine solution (unless previously done before application of a primer coat) using at least 1500 P.S.I. to remove all previous coatings, dirt, grease, and other foreign materials, especially mold, mildew and algae. **KOOL-KOTE™** will resist mildew growth but will not kill mildew already on the surface. Apply it only to a sound, well prepared roof surface. Patch any holes, cracks, flashings, valleys, vents, etc., with **PERMAPATCH™**, a waterproof caulk and sealant. Tape and seal all seams with **PERMATAPE™**, a polyester fabric tape.

**APPLICATION PROCEDURE:**

Stir **KOOL-KOTE™** well before using. Do not thin, use product as is. Do not apply when temperatures are below 45 degrees Fahrenheit or when humidity is very high. Do not apply when coating will be subjected to rain or heavy dew before it has had enough time to dry (approximately 4 to 6 hours). Drying time will vary depending on temperature, humidity and location. Apply using brush, roller or spray. Spread uniformly and do not allow puddling. Wait at least 12 hours before applying a second coat. Two coats are recommended for optimum performance.

**AIRLESS SPRAYERS:**

Use at least a 1 gallon per minute piston type airless Sprayer with a minimum tip size of .025. Remove all line filters and gun filters before spraying.

**CLEAN UP:**

Clean up all spills, tools and overspray immediately while the coating is still wet with warm soapy water.

Ambient Temperature of 77°F and RH of 50%

**TECHNICAL SPECIFICATIONS:**

Rates & Times May Vary Beyond Specifications

FINISH:	Flat	SPREAD RATE:	100 to 150 sq.ft./gal.
COLOR:	White (Tintable)	DRY to TOUCH:	4 to 6 Hours
VEHICLE TYPE:	Copolymer Emulsion	RECOAT:	12 Hours
SOLIDS by WEIGHT:	55% +/- 2%	CURE TIME:	5 to 7 Days
SOLIDS by VOLUME:	38% +/- 2%	SIZES:	1 Gal., 5 Gal., 55 Gal.
V.O.C.'s (averages):	.37 lbs/gal 44.0 gr/lt	GALLON WEIGHT:	11.6 lbs. +/- .3 lbs.

*Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.*



# MATERIALS HEALTH, SAFETY AND ENVIRONMENTAL DATA SHEET

**MSDS#:  
7000**

<b>Product Identification</b>	Product Name: <b>KOOL-KOTE™</b> Product Code #: <b>7000</b> General Usage: Exterior Latex Roof Coating General Description: Pigmented Latex Coating C.A.S. Number: None Established; Mixture														
<b>Manufacturer Information</b>	Manufacturer's Name: Nationwide Protective Coating Mfrs., Inc. Address: 7106 24th Court East; Sarasota, FL 34243-3993 Emergency Telephone: 1-800-423-7264 or 941-753-7500 Information: 1-800-423-7264 or 941-753-7500 Web Site: www.nationwidecoatings.com      E-Mail: info@natcoat.net Date Effective: January 1 <sup>st</sup> , 2005														
<b>Chemical and Physical Properties</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Color: White</td> <td style="width: 50%;">Odor: Pungent Odor</td> </tr> <tr> <td>Physical State: Liquid</td> <td>Odor Threshold: Unknown</td> </tr> <tr> <td>Boiling Point: 212 Fahrenheit</td> <td>Melting Point: N/A</td> </tr> <tr> <td>Specific Gravity (H<sub>2</sub>O=1): &gt;1</td> <td>Freezing Point: 32 Fahrenheit</td> </tr> <tr> <td>Vapor Presence: about same as H<sub>2</sub>O</td> <td>Solubility in H<sub>2</sub>O: Soluble</td> </tr> <tr> <td>Percent Volatile: 38-43%</td> <td>pH (undiluted): 8 to 8.5</td> </tr> <tr> <td>Evaporation Rate (Butyl Acetate=1): &lt;1</td> <td>Vapor Density (Air=1): &lt;1</td> </tr> </table>	Color: White	Odor: Pungent Odor	Physical State: Liquid	Odor Threshold: Unknown	Boiling Point: 212 Fahrenheit	Melting Point: N/A	Specific Gravity (H <sub>2</sub> O=1): >1	Freezing Point: 32 Fahrenheit	Vapor Presence: about same as H <sub>2</sub> O	Solubility in H <sub>2</sub> O: Soluble	Percent Volatile: 38-43%	pH (undiluted): 8 to 8.5	Evaporation Rate (Butyl Acetate=1): <1	Vapor Density (Air=1): <1
Color: White	Odor: Pungent Odor														
Physical State: Liquid	Odor Threshold: Unknown														
Boiling Point: 212 Fahrenheit	Melting Point: N/A														
Specific Gravity (H <sub>2</sub> O=1): >1	Freezing Point: 32 Fahrenheit														
Vapor Presence: about same as H <sub>2</sub> O	Solubility in H <sub>2</sub> O: Soluble														
Percent Volatile: 38-43%	pH (undiluted): 8 to 8.5														
Evaporation Rate (Butyl Acetate=1): <1	Vapor Density (Air=1): <1														
<b>Fire Protection Information</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Decomposition/Combustion:</td> <td style="width: 50%;">N/A</td> </tr> <tr> <td>Flash Point:</td> <td>N/A; Does Not Burn</td> </tr> <tr> <td>Recommended Extinguishing Media:</td> <td>N/A</td> </tr> <tr> <td>Flammable Limits:</td> <td>N/A</td> </tr> </table>	Decomposition/Combustion:	N/A	Flash Point:	N/A; Does Not Burn	Recommended Extinguishing Media:	N/A	Flammable Limits:	N/A						
Decomposition/Combustion:	N/A														
Flash Point:	N/A; Does Not Burn														
Recommended Extinguishing Media:	N/A														
Flammable Limits:	N/A														
<b>Storage and Reactivity</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Hazardous Polymerization:</td> <td style="width: 50%;">Will Not Occur</td> </tr> <tr> <td>Storage Conditions:</td> <td>Keep from Freezing</td> </tr> <tr> <td>Toxic Products Which May Form:</td> <td>None</td> </tr> </table>	Hazardous Polymerization:	Will Not Occur	Storage Conditions:	Keep from Freezing	Toxic Products Which May Form:	None								
Hazardous Polymerization:	Will Not Occur														
Storage Conditions:	Keep from Freezing														
Toxic Products Which May Form:	None														
<b>Transportation</b>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Hazard Classes:</td> <td style="width: 50%;">None; Not Hazardous</td> </tr> <tr> <td>Hazard Labels:</td> <td>Not Required</td> </tr> <tr> <td>Hazard Determination:</td> <td>MSD Sheet</td> </tr> <tr> <td>Shipping Containers:</td> <td>Varies</td> </tr> <tr> <td>Shipping Class:</td> <td>Class 55; Water Based Paint</td> </tr> </table>	Hazard Classes:	None; Not Hazardous	Hazard Labels:	Not Required	Hazard Determination:	MSD Sheet	Shipping Containers:	Varies	Shipping Class:	Class 55; Water Based Paint				
Hazard Classes:	None; Not Hazardous														
Hazard Labels:	Not Required														
Hazard Determination:	MSD Sheet														
Shipping Containers:	Varies														
Shipping Class:	Class 55; Water Based Paint														
<b>Container Labeling</b>	Explanation of Unique Labeling System:      None Used														

<b>Health Hazard Data</b>	SHORT TERM EXPOSURE	
	Route of Entry: Inhalation: Skin: Eyes: Ingestion:	Precautionary Treatment Expected None Expected None  Flush Immediately with large amounts of water for at least 15 minutes, holding eyelids open. Call a physician if irritation persists  Call a physician if significant amounts have been Swallowed. Give patient large amounts of water or milk for dilution.
<b>Personal Protection</b>	LONG TERM EXPOSURE	
	Carcinogen: Target Organ Effects: Other Health Hazards:	None None None Known
<b>Spill or Leak Protection</b>	Respiratory Protection: Protective Clothing: Ventilation: Other Protective Measures: Eye Protection:	No inhalation hazard expected None Required Local None Safety Glasses
<b>Treatability</b>	Biodegradability: With water prior to cure. Influence on Biological Wastewater Treatment: None Other Impacts on Wastewater Treatment: None Recommended Wastewater Treatment: Dilutable Constituents Interfering With or Not Amenable to Biological or Wastewater Treatment: None	
<b>Recommended Waste Disposal</b>	Dispose of in accordance with Federal, State and Local guidelines.	

**EMERGENCY & INFO: 1-800-423-7264**

*Form based on O.S.H.A. Form 20. Information presented herein has been compiled from sources to be reliable and is accurate and reliable to be the best of our knowledge and belief but is not guaranteed to be so.*

**EMERGENCY & INFO: 941-753-7500**