



FLEECE BACKED
PERMASTIK™
SELF-ADHERING
ROOF REPAIR & SEAM TAPE

PRODUCT DATA

4" x 50' #9500

04/01/20

PRODUCT DESCRIPTION:

PERMASTIK™ Premium Roof Repair Tape is a self-adhesive repair and flashing tape designed to immediately stop leaks and make a variety of roofing and waterproofing repairs. It will adhere to metal, wood, structural concrete, concrete block, brick, smooth BJR, smooth SBS, smooth APP, EPDM, TPO, Hypalon and PVC roofs. Manufactured with select thermoplastic elastomers, **PERMASTIK™** Premium Roof Repair Tape provides a tough and durable repair. It's pressure sensitive properties allow a fast, clean and easy application.

PERMASTIK™ USES:

PERMASTIK™ can be used on: metal, wood, concrete, block, brick, built-up-roofs, SBS smooth (Styrene-Butadiene-Styrene modified bitumen), EPDM and most other roofing substrates.
PERMASTIK™ is compatible to be top coated with most any Nationwide Protective Coating product.

SURFACE PREPARATION:

Substrate should be clean, dry and free of dew, frost, oil, salt, dust and rust. Clean area first with a cloth and cleaner. On metal roofs power wash and scrub with detergent to remove any oil or grime. Use a wire brush to remove rust and prime with **METAL-PRIME RED-OX™** Red Iron Oxide Metal Primer. For best results in cold temperature application, keep rolls in a warm environment and warm the substrate with hot air prior to application.

APPLICATION PROCEDURE:

Cut to length. Shorter lengths (less than 4 ft) are easier to work with unless using a team of two or more applicators. Remove release film. Press in place using a gloved hand or a steel roller. Apply the exact length to predetermined location. Tape cannot be peeled up and reset. Always roll from the center out to remove trapped air pockets and fish mouths. Start in corners to eliminate "tenting". Coat adhered tape the same day with most any Nationwide Protective Coating product according to product instructions. Coat a minimum of 2" past tape on all sides on substrate. Selection of Nationwide Protective Coating product will depend on type of existing roof and application. Always follow application instructions and coverage rates on product labels.

PRECAUTIONS:

PERMASTIK™ will not adhere to silicone surfaces. For best results test adhesion on surfaces before applying. Do not store at temperatures above 100°F.

PHYSICAL PROPERTIES

PEEL STRENGTH:	21 lbs. + per inch of width
APPLICATION TEMPERATURE:	40°F to 200°F
PERMEABILITY:	.001 perms max
ELONGATION:	750%
TENSILE BREAK:	800 +/- 50 psi

TECHNICAL SPECIFICATIONS:

FINISH:	Matte	ROLL SIZE(s) (inches):	4" x 50 Feet
FABRIC:	Polyester Fleece	BULK:	35.0 mils
WEIGHT per ROLL:	4.0 Pounds	PACKAGING:	4": Case of 12 Rolls

Information presented on this Data Sheet has been compiled from sources to be reliable, and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so.

In Any Event Nationwide Protective Coating Manufacturers, Inc. will not be liable or responsible for any past, present or future leaks or any resulting consequential or incidental damages.